

PATENT APPLICATION BASED ON: Docket Number 78990DMW

Inventor(s): Robert L. Baldino

Attorney: David M. Woods

Document ID: \DOCKETS\78990\APPL.DOC

METHOD AND APPARATUS FOR PRODUCING DIGITAL IMAGES
WITH EMBEDDED IMAGE CAPTURE LOCATION ICONS

EASTMAN KODAK COMPANY
RESTRICTED INFORMATION

"Express Mail" mailing label number EL267106131US
Date of Deposit December 20, 2000

I hereby certify that this paper or fee is being deposited
with the United States Postal Service "Express Mail Post
Office to "Addressee" service under 37 CFR 1.10 on the date
indicated above and is addressed to the Commissioner of
Patents and Trademarks, Washington, D.C. 20231

Robin G. Reeves

(Typed or printed name of
person mailing paper of fee)

Robin G. Reeves

(Signature of person mailing paper or fee)

METHOD AND APPPARATUS FOR PRODUCING DIGITAL IMAGES WITH EMBEDDED IMAGE CAPTURE LOCATION ICONS

FIELD OF THE INVENTION

5 The present invention generally relates to digital images, especially with regard to their reproduction in an interactive environment such as via computers and wide area networks such as the Internet.

BACKGROUND OF THE INVENTION

10 Digital images have become commonplace in interactive media such as web pages on the World Wide Web. In many systems the image is captured by a digital camera and stored as an image file, which an online user can later view.

 Prior art digital image display systems have recognized that
15 users/viewers often have an interest in knowing from where an image is captured (the location of image recording device when the image was recorded). To accomplish this, some prior art digital image display systems require manual entry of information identifying the capture location in the form of a header or "watermark" in the image file. While this may give one who receives the image file an
20 indication of where the image emanates, the user may still have to use great imagination to picture the location of capture. Additionally, the header information may not be in a user-friendly format, making deciphering necessary. Further, such systems are prone to mistakes due to human error in entering the capture location data.

25 One method of improving on the previously described system is to automate the capture location information gathering process by harnessing automatic location systems. For example, the Global Positioning Satellite (GPS) is a well-known method for pinpointing the location of a particular GPS receiver with a fairly high degree of accuracy. Other methods include the use of Radio Triangulation (RT) systems. Using such an approach, a GPS receiver can be either in-
30 corporated in the hardware of the digital camera, or located nearby. A subsequent image file will contain not only the raw image data, but also a date and time

stamp, along with header information related to the location of the GPS receiver when the image is collected. While this approach may eliminate human errors, and introduce a higher degree of capture location accuracy, the header may still be difficult to decipher and the viewer is still required to use his/her imagination
5 picturing the environs of the image capture location.

Thus, there is a great need wholly unaddressed by the prior art to provide a digital image capture and display system wherein the viewer of a digital image can also have an easy, user-friendly way to visualize the image capture location.

10

SUMMARY OF THE INVENTION

In view of the aforementioned problems and deficiencies of the prior art, the present invention provides a method for producing a digital image for display. The method at least includes the step of receiving position information
15 corresponding to a geographical location where the digital image is captured. The method also novelly includes the steps of converting the position information into at least one user perceivable image capture location icon, and generating a display. The display at least includes the digital image and a capture location iconic region having at least one graphical image capture location icon.

20

The present invention also provides a system for producing a digital image for display. The system at least includes a position information receiver adapted to receive position information corresponding to a geographical location where the digital image is captured. The system also novelly includes an image capture location icon generator adapted to convert the position information into at
25 least one user perceivable image capture location icon, and a display generator adapted to generate a display. The display at least includes the digital image and a capture location iconic region, which may be user definable, having at least one graphical image capture location icon.

BRIEF DESCRIPTION OF THE DRAWINGS

Features and advantages of the present invention will become apparent to those skilled in the art from the description below, with reference to the following drawing figures, in which:

5 Figure 1 is an example of a displayed digital image having a present-inventive image capture location iconic region, and one or more present-inventive image capture location icons;

 Figure 2 is a more detailed version of the present-inventive image capture location iconic region and image capture location icons;

10 Figure 3 is an example of image capture location icons which can be included in the present-inventive image capture location iconic region; and

 Figure 4 is a schematic block diagram of the basic hardware for producing the present-inventive digital images with embedded image capture location iconic regions, and image capture location icons.

15

DETAILED DESCRIPTION OF THE INVENTION

As will be described below in more detail, the present invention novelly converts the capture location data included in an image file into one or more icons having a likeness corresponding to the geographic region of capture.

20 The icon is automatically chosen from a library of capture location icons. In the preferred embodiment, a user/sponsor responsible for hosting the digital image (such as via a web site) can also add custom icons representing, for example, showing a particular attraction, institution, building or other physical indicia. The capture location icons are embedded in the displayed digital image in a layered
25 fashion.

 Figure 1 illustrates a digital image display 100 produced in accordance with the present invention. The display 100 might appear, for example, on a web page. Alternatively, the display 100 might be produced by the computer of an online user having application software for producing a display according to
30 the present invention, when the user downloads an image file with GPS metadata. Per the present invention, the display 100 includes a digital image 102 and an im-

age capture location iconic region 104, which includes one or more layers of linked image capture location icons 106.

An image capture location icon 106 contains a picture representing the geographic location where the image was captured. In the preferred embodiment, the layers of image capture location icons are hierarchically arranged from a picture representing the most general geographic location on the top layer, to a picture representing the most specific geographic location on the bottom layer. This is more apparent from viewing Figures 2 and 3, where several icons 106.1 through 106.n are shown.

The icon 106.1—the first one seen by a user/viewer—is the most general one in the preferred embodiment. It shows a picture of a broad geographic region such as the continent from which the image was captured. For example, if the image was captured in the United States of America, the icon 106.1 might be a map (a simple map or an outline) with the continental United States prominently displayed. The icons have regions which can be activated with a pointing device such as a “mouse” to move to another icon with greater location specificity.

As an example, the digital image might be from the U.S. Space Camp in Huntsville, Alabama, United States of America. In this case the icon 106.1 is a picture or map of the United States. The user can click on a star or other indicia, or anywhere within the icon, to activate the next icon layer 106.2 to display a map of the State of Alabama. The next layer 106.3 might be a map or picture of the City of Huntsville, and can be activated by clicking within the icon 106.2.

Along with the standard icons which can be automatically inserted from an image capture location icon library, the application or data server hosting the digital image can also include custom icons providing more information about the capture location. In the U.S. Space Camp example, the host application or server can include an icon 106.4 representing U.S. Space Camp as the next layer, followed by a layer 106.5 representing a particular exhibit, such as “History of Rockets.” The last layer 106.n in the example might be a hyperlink to a web page containing more information about an attraction, products or the like of the web

page sponsor, so that an online user can connect to the web page for further information.

In the example above, a user viewing images with an application on a host displaying digital images according to the present invention, might see a picture of rocketry artifacts. Within the larger picture is an iconic region 104
5 where the icons 106 are superimposed. The online user interested in the origin of image can click on the icons 106 for visual, user-friendly information.

Figure 4 details the preferred embodiment for a system 400 for capturing and displaying digital images according to the present invention. A
10 digital still camera 402 that captures digital images to be displayed has some or all of the following general components, as will be understood by those skilled in the art: a lens 404 for capturing the light representing an image; a charge-coupled device (CCD) image sensor 406 or other electronic image capture device for converting the light into an analog electrical signal; an analog-to-digital (A/D) con-
15 verter 408 for converting the analog signal into a digital signal; a processor 410 for receiving the digital image and controlling the overall operation of the camera 402; an image Dynamic RAM (DRAM) 416 for dynamically storing images; a memory card interface 412; a removable memory card 414; a serial, parallel or data interface 418; various user control buttons 420; and a liquid crystal display
20 (LCD) 422 for displaying interactive information and/or images to the camera user.

In accordance with the present invention, the system 400 also includes a position information receiver module 424. The position receiver is a GPS receiver in the preferred embodiment, but can use other types of location technology as well, such as Radio Triangulation (RT). While the GPS receiver is shown
25 as a separate unit in Figure 4, those skilled in the art will appreciate that it is possible to include the GPS receiver inside of the digital camera. The GPS receiver module 424 supplies the processor 410 with precise latitude and longitude information via the serial or other digital interface 418. When an image frame is cap-
30 tured and digitized, along with date and time stamping the image information, the processor also adds location information (or location "metadata") to the image

data in an image file to be stored in memory 414. The location information is stored either in the form of a header entry or a watermark in the image, or both.

5 A display circuit 426 receives the digital image file for further processing from the memory card 414 via a memory card reader 428, or other means of data transfer. It will be appreciated by those skilled in the art that that the memory card 414 and the memory card reader 428 can be replaced by a permanent memory, and a communication link, respectively. A personal computer and application software can subsume the display circuit. In the preferred embodiment, the display circuit 426 is part of a personal computer operated by an
10 online/offline user/customer who receives or loads digital image files with GPS metadata. In an alternate embodiment, the display circuit 426 is part of an application server for hosting a web page displaying digital images in accordance with the present invention, as shown in Figures 1-3. Using this latter approach, online users need not have special application software on their computers to enable
15 them to view the image capture location icons of the present invention.

A display circuit CPU 430 receives the image file for further processing needed for display. A library of special icons corresponding to predefined GPS latitude-longitude combinations (from the GPS metadata) supplies pre-existing icons to the CPU for display. In the preferred embodiment, the icon library as well as application software reside on the hard drive 440 or application
20 server or on a web site.

The display 436, display control (e.g., keyboard) 438, modem 442, printer 444 and hard drive 440 all have the typical functions of a computer system. In this arrangement, the hard drive 440 can of course store images in the iconic
25 form of the present invention, while the modem 442 could operate to, among other things, connect the display computer to a source for digital images with GPS location data, such as the Internet or other wide area networks. This could also be accomplished by use of a network interface card, LAN or WAN, wired or wireless.

30 Variations and modifications of the present invention are possible, given the above description. However, all variations and modifications which are obvious to those skilled in the art to which the present invention pertains are con-

Year	1961	1962	1963	1964	1965	1966	1967	1968	1969	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100																																					
Population	1,000,000	1,050,000	1,100,000	1,150,000	1,200,000	1,250,000	1,300,000	1,350,000	1,400,000	1,450,000	1,500,000	1,550,000	1,600,000	1,650,000	1,700,000	1,750,000	1,800,000	1,850,000	1,900,000	1,950,000	2,000,000	2,050,000	2,100,000	2,150,000	2,200,000	2,250,000	2,300,000	2,350,000	2,400,000	2,450,000	2,500,000	2,550,000	2,600,000	2,650,000	2,700,000	2,750,000	2,800,000	2,850,000	2,900,000	2,950,000	3,000,000	3,050,000	3,100,000	3,150,000	3,200,000	3,250,000	3,300,000	3,350,000	3,400,000	3,450,000	3,500,000	3,550,000	3,600,000	3,650,000	3,700,000	3,750,000	3,800,000	3,850,000	3,900,000	3,950,000	4,000,000	4,050,000	4,100,000	4,150,000	4,200,000	4,250,000	4,300,000	4,350,000	4,400,000	4,450,000	4,500,000	4,550,000	4,600,000	4,650,000	4,700,000	4,750,000	4,800,000	4,850,000	4,900,000	4,950,000	5,000,000	5,050,000	5,100,000	5,150,000	5,200,000	5,250,000	5,300,000	5,350,000	5,400,000	5,450,000	5,500,000	5,550,000	5,600,000	5,650,000	5,700,000	5,750,000	5,800,000	5,850,000	5,900,000	5,950,000	6,000,000	6,050,000	6,100,000	6,150,000	6,200,000	6,250,000	6,300,000	6,350,000	6,400,000	6,450,000	6,500,000	6,550,000	6,600,000	6,650,000	6,700,000	6,750,000	6,800,000	6,850,000	6,900,000	6,950,000	7,000,000	7,050,000	7,100,000	7,150,000	7,200,000	7,250,000	7,300,000	7,350,000	7,400,000	7,450,000	7,500,000	7,550,000	7,600,000	7,650,000	7,700,000	7,750,000	7,800,000	7,850,000	7,900,000	7,950,000	8,000,000	8,050,000	8,100,000	8,150,000	8,200,000	8,250,000	8,300,000	8,350,000	8,400,000	8,450,000	8,500,000	8,550,000	8,600,000	8,650,000	8,700,000	8,750,000	8,800,000	8,850,000	8,900,000	8,950,000	9,000,000	9,050,000	9,100,000	9,150,000	9,200,000	9,250,000	9,300,000	9,350,000	9,400,000	9,450,000	9,500,000	9,550,000	9,600,000	9,650,000	9,700,000	9,750,000	9,800,000

5

PARTS LIST

100	Digital image display
102	Digital image
104	Image capture location iconic region
106	Image capture location icons
106.1	Continent of image capture icon
106.2	State/territory of image capture icon
106.3	City/town/local region of image capture icon
106.4	User-chosen general location icon
106.5	User-chosen specific location icon
106.n	Hyperlink to user-chosen web page icon
400	System for capturing and displaying digital images
402	Digital still camera
404	Camera lens
406	CCD image sensor
408	Analog-to-Digital Converter
410	Processor
412	Memory card interface
414	Memory card
416	Image Dynamic RAM
418	Serial interface
420	User control buttons
424	Position information receiver module
426	Display circuit
428	Memory card reader
430	Display circuit CPU
432	CD-ROM
434	CD-ROM drive
436	Display
438	Display control
440	Hard drive

[illegible]